

NT 65/2 TACT²

The Kärcher Tact² systems are ever popular as specialist systems and as all-rounders thanks to their high level of mobility and excellent performance, their solid construction and their wide range of practical design features. The NT 65/2 Tact² is supplied with the entire antistatic package as standard. The system tackles even large amounts of fine dust.



Order No. 1.667-286.0

- Automatic Filter Cleaning System Tact²
- Fully antistatic
- Adjustable push handle


Technical data

EAN code		4039784714953
Type of current	Phases / Volt / Hertz	1 / 220 - 240 / 50 - 60
Air flow	Litres per second	2 × 74
Vacuum	Millibar / Kilopascal	254 / 25.4
Container capacity	Litre	65
Container material		Plastic
Rated input power	Watt	Maximum 2760
Standard nominal width		DN 40
Cable length	Metre	10
Sound pressure level	Decibel	73
Colour		anthracite
Weight without accessories	Kilogram	24.5
Weight incl. packaging	Kilogram	31.332
Dimensions (L × W × H)	Millimetre	575 × 490 × 880

Equipment


Suction hose length	Metre	4
Suction hose type		electrically conductive
Bend		electrically conductive
Quantity of suction tubes	Unit	2
Suction tubes length	Millimetre	550
Suction tubes material		Stainless steel
Wet/dry floor nozzle width	Millimetre	360
Crevice nozzle		■
Drain hose (oil-resistant)		■
Auto shutdown when max. level is reached		■
Fully antistatic		■
Flat pleated filter		Paper
Filter cleaning		Automatic Filter Cleaning System Tact ²
Sturdy bumper		■
Push handle		■
Protection class		I
Castor with brake		■

■ included in delivery.



Easy transport

- Adjustable push handle and large wheels make transport easy even on uneven surfaces.



Smart accessory storage

- For example, the floor tool can be quickly fixed any way round.



Automatic Filter Cleaning System Tact²

- This divided flat pleated filter is cleaned by air blasts and can be removed from the clean side.
- Fine dusts cannot block the filter. A constant high air flow is maintained.
- Over 1000 kg of category A fine dust can be vacuumed without the need to change the filter.

EQUIPMENT FOR NT 65/2 TACT²

1.667-286.0



		Order No.	Description	
FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M				
Flat pleated filter (paper)				
Flat pleated filter (paper)	1	6.907-276.0	Flat pleated filter dust class M, nano-coated paper. Suitable for fine dust and dry dirt pick up.	■
Flat pleated filter (PES)				
Flat pleated filter (PES)	2	6.907-277.0	Flat pleated filter dust class M, rotproof PES fleece. Suitable for frequent wet pick up.	□
FILTER BAGS				
Paper filter bags				
Paper filter bags, 5 Unit, NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC	3	6.904-285.0	Premium 3-layer paper filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack.	□
FILTER T/ NT				
Flat pleated filter HEPA, dust class H				
HEPA flat pleated filter	4	6.904-364.0	For Kärcher wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter. Suitable for vacuuming hazardous dusts, coarse dirt and liquids.	□
Special filter bags, wet filter bags				
Wet filter bag	5	6.904-252.0	Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Membrane filter / fabric filter				
Membrane filter, NT 65, NT 70, NT 72, NT 75, NT 551, NT 602, NT 700, NT 702, NT 802, NT 993	6	6.904-282.0	Polyester needle fleece membrane/fabric filter – BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	□
BENDS				
Plastic bend				
Plastic bend	7	5.031-718.0	DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
	8	5.031-939.0	Electrically conductive DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
	9	5.032-427.0	Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
Bend metal				
Bend, DN 35, metal	10	6.900-519.0	DN 35 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	□
SUCTION NOZZLES				
All-purpose nozzles (wet/dry)				
Floor tool anthracite packaged NW35	11	2.889-173.0	300 millimetre width, anthracite coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Incl. brush strips and squeegees.	□
Floor tool neutrally DN40	12	6.906-383.0	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
Crevice nozzles				
Crevice nozzle packaged NW35	13	2.889-130.0	Plastic crevice nozzle.	□
Crevice nozzle	14	6.900-922.0	Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR NT 65/2 TACT²

1.667-286.0



		Order No.	Description	
SUCTION NOZZLES				
Pipe dusting nozzles				
BRUSH	15	6.903-035.0	Plastic, pipe diameter 100 mm	☐
	16	6.903-036.0	Plastic, pipe diameter 200 mm	☐
SUCTION TUBES				
Suction tubes stainless steel				
Suction tube, DN 35, 505 mm, stainless steel	17	6.902-154.0	Suction tube made of high-quality stainless steel in DN 35 and 505 mm long for wet and dry vacuum cleaners from Kärcher.	☐
Suction tubes metal				
Suction tube, NT, DN 35, 505 mm long, chrome-plated steel, suitable for: NT 25/1, NT 27/1, NT 30/1, NT 35/1, NT 40/1, NT 48/1, NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/1, NT 75/2, NT 611, NT 802 IV	18	6.900-514.0	The suction tube made of chrome-plated steel (DN 35, 505 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.	☐
SUCTION HOSES				
Suction hoses with clip system 1.0 (compatible with vacuum cleaners up to model year 2016)				
Repair set, C 40	19	2.639-873.0	Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	☐
Suction hose	20	6.906-321.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)				
Hose electrically conducting packaged NW	21	2.889-137.0	The electrically conductive suction hose in nominal width DN 35 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	☐
CONNECTING SLEEVES				
Adapter for electric power tools, clip on, el.				
Sleeve for tool C35EL	22	5.453-042.0	3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	☐
Reducing sleeves				
Reducer adapter from DN 40 to DN 35	23	6.902-017.0	Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	☐
Reducer from ID 35 to 32	24	6.902-072.0	Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐
OTHER ACCESSORIES FOR T AND NT				
CS 40 Me	25	2.863-026.0	The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	☐

☐ Available accessories.