

B 260 R I BP PACK+R120+DOSE+SB

Excellent vacuuming results, 10 km/h driving speed and designed for tough industrial applications: the ride-on scrubber drier B 260 RI Bp Pack with a battery and an external charger as standard.



Made in Europe



SIDE BROOM



DOSE



ROLLER BRUSH HEAD



WHEEL ANGLE SENSOR

Order no.

1.480-256.0

- EASY Operation selector switch

Technical data

EAN code		4054278954349
Drive type		Battery
Traction drive		Traction motor
Working width of brushes	cm	120
Working width with 1 side brush	mm	1420
Working width with two side brushes	mm	1420
Working width, vacuuming	cm	134
Tank of fresh/dirty water		260 / 260
Waste container	l	32
Theoretical area performance	m ² /h	max. 12000
Practical area performance	m ²	8400
Battery type		Low-maintenance
Battery	V / Ah	36 / 630
Battery runtime	h	max. 5
Battery charging time	h	approx. 12
Driving speed	km/h	max. 10
Climbing ability	%	max. 15
Brush rotational speed	rpm	1250
Brush contact pressure	kg / g/cm ²	150 / 168
Aisle turning width	cm	212
Water consumption	l/min	max. 9
Sound pressure level	dB(A)	73
Total permissible weight	kg	1840
Weight without accessories	kg	1448

Equipment

Roller brush	Piece(s)	2
Auto Fill		■
Powerful traction drive		■
Battery and charger included		■
Automatic water stop		■
DOSE		■
Parking brake		■
Integrated sweeper		■
Adjustable steering wheel		■
Sweeping function		■
Solenoid valve		■
Squeegee, curved		■
Side brush		■
2-tank system		■
standard daytime driving light		■
Type of suction lips		Linatex®
dosing canister for cleaning agent with closed loop system		■
Kärcher colour and operating concept		■
Kärcher Intelligent Key System (KIK) with over 30 user languages and individual user rights		■
Home Base fastening possibilities for mop or similar		■
speed reduction in curves for increased safety		■

Dimensions (L × W × H) mm 2000 × 1380 × 1570

electrical and mechanical float switch

Easy Operation selector switch

■ included in the scope of supply.

Users must receive training on this device.



Newly developed roller brush head

- Greatly improved sweeping results and prevents squeegee blockages.
- The rollers can be changed in a matter of seconds and without tools.
- Excellent cleaning results.



10 km/h driving speed

- Enables a high area performance in next to no time and quick transportation operations.
- The steering angle sensor acts as a safety feature when driving in curves.
- There is automatic braking if speed is too high when driving in curves.



Includes two turbines as standard

- Excellent vacuuming results on all surfaces.
- Wear-free Ec turbines.
- Optimised airflow with the newly developed squeegee.


ACCESSORIES FOR B 260 R I Bp PACK+R120+DOSE+SB 1.480-256.0



		Order no.	Description	
ROLLER BRUSHES				
Roller brush, medium, red, 1118 mm	1	4.250-181.0	Red standard roller brush for maintenance cleaning.	■
Roller brush, very hard, Black, 1118 mm	2	5.250-489.0	Very abrasive roller brush for the deep cleaning of hard-wearing floor coverings with very sticky dirt.	□
BRUSH HEADS				
Brush head R 120 Industry	3	2.763-058.0	The brush head with 2 roller brushes, 120 cm working width and integrated pre-sweeping function is ideal for cleaning stubborn dirt and its brush can be replaced without any tools.	■
WIPING FLAPS				
Linarid squeegee blades	4	4.250-167.0	Set of tear-resistant squeegee blades made of Linarid. They keep the cleaning water in the working area of the brush head and ensure optimum squeegee performance in turning manoeuvres.	■
Squeegee blades, oil-resistant	5	4.250-166.0	Set of low-wear, oil-resistant squeegee blades made from polyurethane. For optimum cleaning results with curve movements and reliable keeping of the cleaning water in the working area of the brush head.	□
SQUEEGEES AND SQUEEGEE BLADES				
Squeegees				
Squeegee, 1340 mm, parabolic	6	4.777-110.0	Parabolic, robust squeegee made from aluminium with 1340 mm suction width and quick coupling. Delivers excellent suction and drying results. Tool-free change of suction lips.	■
Squeegee blades				
Suction lips, Linatex®, 1490 mm	7	4.250-178.0	Tear-resistant suction lip made from Linatex® with special inlet openings for optimal suction results at crevices and joints. Suitable for parabolic squeegee with 1340 mm suction width.	■
Suction lips, oil-resistant, slotted, 1490 mm	8	4.250-179.0	Low-wear, oil-resistant suction lip made from polyurethane. Three-layer material for high level of flexibility and optimum cleaning properties. For parabolic squeegee with 1340 mm suction width.	□
KITS				
Side broom / side scrub deck mounting kit				
Side brush B 260 RI R120	9	2.644-372.0	Side brush, right and left. Includes lifting motor and deflector. Removes loose dirt around edges.	■
Other attachment kits				
Side brush spray nozzle attachment kit	10	2.644-392.0	Attachment kit for retrofitting the B 260 R ride-on scrubber dryer with side brushes. The spray nozzles are dust-binding and thereby reduce the amount of dust stirred up when using the side brushes.	□
Squeegee impact protection	11	2.644-369.0	Impact protection for our B 260 RI ride-on scrubber drier. Prevents damage to the squeegee when reversing and prevents collisions with tall obstacles, such as palletes.	□
Connection to a vacuum cleaner or high-pressure cleaner	12	2.644-370.0	Attachment kit for the B 260 RI ride-on scrubber dryer to attach the HD 4/11 C Bp Pack high-pressure cleaner or the NT 22/1 Ap Bp Pack wet and dry vacuum cleaner.	□
Protective roof	13	2.643-849.0	This high-quality protective roof for the B 250 R scrubber drier (height 2,170 mm including protective roof) protects the operator from falling objects - tested in accordance with EN IEC 60335-2-72.	□
2-point safety belt	14	6.989-732.0	Two-point safety belt for ride-on scrubber drier types B 250 R and B 250 R I. Considerably increases work safety for the operator.	□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR B 260 R I BP PACK+R120+DOSE+SB 1.480-256.0



		Order no.	Description	
KITS				
Dose mounting kit				
Detergent dosing unit attachment kit DOSE B260RI	15	2.644-368.0	Attachment kit for Kärcher scrubber dryers for the detergent dosing unit between 0.5 and 3% directly from up to 2x 10-l canisters. With filling level indicator on the device display.	<input type="checkbox"/>
Lighting / revolving signal light mounting kit				
Flashing beacon B 260 RI	16	2.644-363.0	Flashing beacon attachment kit for Kärcher scrubber dryers. Improves visibility during cleaning applications and thus increases safety in the working environment.	<input type="checkbox"/>
Blue spotlight front B260RI	17	2.644-366.0	Blue spotlight attachment kit for B 260 RI ride-on scrubber dryer. Projects a blue spot onto the floor in front of the machine for enhanced safety, e.g. in high-bay warehouses.	<input type="checkbox"/>
Blue spotlight rear B260RI	18	2.644-367.0	Blue spotlight attachment kit for B 260 RI ride-on scrubber dryer. Projects a blue spot onto the floor behind the machine for enhanced safety, e.g. in high-bay warehouses.	<input type="checkbox"/>
SIDE BRUSHES				
Standard side brushes				
Standard side brush	19	6.905-986.0	Standard side brush with moisture-proof universal bristles for normal soiling on all surfaces. Extremely durable.	<input checked="" type="checkbox"/>
TRACTION BATTERIES AND CHARGERS				
Batteries				
Battery kit 525 Ah/36 V li-ion	20	2.654-000.0	525 Ah lithium iron phosphate battery with a long manufacturer's guarantee: fast and intermediate charging capability and service life around four times longer than lead batteries. Ideal for continuous operation with fast chargers.	<input type="checkbox"/>
Battery Chargers				
Off-board battery charger 36 V/200 A 330-480 V/50-60 Hz	21	4.654-083.0	200 A/36 V off-board quick charger for the 525 Ah lithium-ion trough battery of the B 260 RI. Can be used with CEE 32 A plug at 330-480 V/50-60 Hz.	<input type="checkbox"/>

■ Included in the scope of supply. □ Available accessories.